

B-TEC[®] GMBH

Geräte u. Anlagentechnik

*Operating instructions and inspection
checklist for spray - gun cleaner*

Typ : Starter-04

Serial number:



B-TEC North America
4901 Prime Parkway • McHenry, Illinois 60050
Phone : 815-759-1612
Fax : 815-759-1615
e-mail: sales@btecna.com
www.btecna.com

1. Table of contents

<i>Page</i>	<i>Description</i>
1	<i>Table of contents</i>
2, 2a	<i>Declaration of conformity</i>
3	<i>Important Informations</i>
4	<i>Approved cleaning agents</i>
5	<i>Technical description / Information</i>
6, 7	<i>Safety Regulation</i>
8	<i>Transport and installation</i>
9	<i>Detailed illustrations</i>
10, 11	<i>Operating instructions</i>
12	<i>Maintenance</i>
13	<i>Blank „Safety Inspection Checklist“</i>

EG - Konformitätserklärung / Declaration of conformity

Manufacturer B-TEC North America
4901 Prime Parkway
McHenry, Illinois 60050

We hereby declare that the machines described herein and the marketed models conform in conception and in design to the relevant fundamental safety and health requirements of the applicable EU directives.

Waschgeräte/gun cleaner: Starter-04

Serien-Nr.: _____ **Baujahr/construction year:** 2007

Die Maschine entspricht folgenden Bestimmungen/ The machines conform to the following regulations::

Richtlinie 98/37/EG, Maschinenrichtlinie
Richtlinie 94/9/ EG, EG-Explosionsschutz-Richtlinie (siehe ergänzendes Blatt im Anhang)
PTB 0102 / R.Nr.: 05 ATEX D 116

Folgende harmonisierende Normen sind angewandt/ The following harmonising norms are applied::

DIN EN 12100-1, DIN EN 12100-2, Sicherheit von Maschinen, Geräten und Anlagen.
DIN EN 294, Sicherheit von Maschinen-Sicherheitsabstände
DIN EN 983, Sicherheitstechnische Anforderungen an fluidtechnische Anlagen und deren Bauteile
-Pneumatik-
DIN EN 13463, Nicht-elektrische Geräte für den Einsatz in explosionsgefährdeten Bereichen

Folgende nationale Normen, Richtlinien und Spezifikationen sind angewandt:

Special national norms are applied:

BGR 180, Richtlinien für Einrichtungen zum Reinigen von Werkstücken mit flüssigen
Reinigungsmitteln
BGV A8, Sicherheits- und Gesundheitsschutzkennzeichnung am Arbeitsplatz

Ort/Datum/Hersteller-Unterschrift

Location/Date/Manufacturer`s signatur

Angaben zum Unterzeichner: Geschäftsführer

Function of the signer: managing director

2.A Protective Measures against Explosion

B-TEC washing devices have been manufactured in accordance with the actual guidelines. The requirements 94/9/ EG (ATEX) have been met technically.

The Norddeutsche Metall-Berufsgenossenschaft, Hannover and PTB, Braunschweig were consulted as advisors.

The following declaration are on the B-TEC type plate:

EX II 2 G c IIA <T6
max. surround temp.: 0-40° C
PTB 05 ATEX D 116

Fundamentally, all B-TEC washing devices are operated by use of compressed air (with the exception of ultrasonic technique).

The following safety instructions and general provisions have to be followed:

- 1. Washing devices may be operated exclusively for their specific purpose.*
- 2. The devices have to be grounded safely with the installed potential compensation cable.*
- 3. Barrels containing solvents or any metal containers must be grounded separately. Please see also BGR 132, 3.6.3.3.*
- 4. If barrels or containers made of plastics are used, the bunghole has to be wiped off extensively with a water-moistened cloth, before the draw in- and drain hoses are inserted or pulled out. The hoses must be inserted in their full length.*
- 5. All users must wear insulating working shoes, their clothing must not create static charge. Within the fire hazard area around the washing devices no activities are permitted, which might create static charge, sparks, or superficial heat up of more than 21° C.*
- 6. The floors in explosion endangered areas have to be insulated.*
- 7. In addition to that, will you please follow the instructions of the respective B-TEC operating manual.*

3. **Important information**

a) *The B-TEC apparatus and machines are only to be used for the purpose expressly described below. Any other use is contrary to regulations. The manufacturer cannot be held liable for damages resulting from such non-regulations use.*

b) **Approved use:**

b) *These apparatus and machines are to be used for cleaning varnish and tumbler-systems as well as paint soiled parts and hand tools using solvents (A I, A II, A III) or non-combustible, aqueous cleaners for water-based varnishes. **Exception: share of Aceton ≥ 65 %.***

The washers are not to be used in continuous operation as for instance in serial production. Improper use of the washers can endanger the healths of the operator and of others and cause damage to the washer itself or to other materials and assets.

c) **Safety inspections:**

c) *On page 20 of this instruction book there is a form for documenting safety inspections at regular intervals. The form is only to be filled out by specialist technicians (persons with sufficient knowledge and experience, manufacturer's mechanics) or experts (e.g. engineers or Technical Control Board* experts).*

Safety inspections must be conducted at least once every year.

d) **Safety advice:**

d) *Important information and danger spots are highlighted in the operating instructions by the symbols „Notice!“ and „Attention!“. Text passages with these symbols must be read very carefully.*

Explanation of the symbols:

„Attention!“ - *You will find this symbol whenever attention is drawn to situations in which danger to life can arise due to or during incorrect or improper operation. Pay special attention to these symbols and act carefully.*

„Notice!“ - *You will find this symbol in the operating manual whenever your attention is to be drawn to correct work procedures, economic ways of operation or when the machines can be damaged by incorrect operation.*

4. Approved cleaning agents

Approved cleaning agents / solvents

- a) highly flammable liquids (hazard class „F“/ R 11) with a flash point under 21° C such as lacquer solvent or regenerated washing solvent but not extremely flammable.
- b) flammable liquids of hazard class - / R 10 with a flash point between 21° C and 55° C.
- c) non-flammable, aqueous cleaning agents (neutral or slightly alkaline pH) such as distilled water for water-soluble varnishes and paints.

Notice! Ask your cleaning agent supplier for the data sheets pertaining to safety matters. These will contain the information about the cleaning agents that you are using

Attention! Never alternately use solvents and cleaning agents fo water-based paints. Follow the manufacturer’s instructions. Alternating the two types of agents can cause gas build up and explosions!

Notice! When changing from solvents to cleaning agents for water-based paints (or vice-versa) the paint gun washer has to be completely cleaned of paint, water and solvent residues.

Technical description:

Starter-04: Washer for automatically cleaning tumbler-systems. The automatic wash cycle is activated by a timer.

All models have a strong exhaust that is automatically turned on an off when the door is opened or closed.

All models are completely air-driven.

Technical data:

Outside dimensions:

Width	mm	670
Depth	mm	510
Height	mm	370

Compressed air connection:

Operating pressure	bar / (p.s.i.)	max. 6 / (87)
--------------------	----------------	---------------

Size of containers standing under the gun-cleaner:

Maximum container size	60 litres	number 2
------------------------	-----------	----------

Noice emission (enveloping curve method):

	dB (A)	76
--	--------	----

Exhaust air volume:

at 6 bar operating pressure	m ³ /h	380
-----------------------------	-------------------	-----

6. Sicherheitsbestimmungen - Achtung !

B-TEC Washers are safe to operate and built according to state-of-the-art technology. Due to the nature of the processes there are processes and parts that cannot be protected without impairing operability and functionality.

Attention ! *The operator must observe and follow the following information sheets pertaining to safety, fundamentals and guidelines whenever using these washers for cleaning spray paint guns or parts.*

BGV AI	<i>General regulations</i>
BGR 500	<i>Working with coating materials</i>
BGV A8	<i>Safety and health protection warnings at the workplace</i>
BGR 114	<i>Guidelines for avoiding dangers arising from an explosive atmosphere gas mixtures with examples - Explosion Guidelines (EX-RL)</i>
BGR 121	
BGI 578	<i>Information sheet: skin protection</i>
BGS 944	<i>Information sheet on first aid for contact with hazardous chemicals</i>
BGR 132	<i>Guidelines for preventing ignition by electrostatic discharges -> Directive „Static Electricity“</i>
BGR 133	<i>Rules for equipping workplaces with fire extinguishers</i>
BGR 621	<i>Information sheet: Solvents</i>
BGR 180	<i>Guidelines for facilities for cleaning workpieces with solvents</i>
BGR 189	<i>Rules for the use of protective clothing</i>
BGR 190	<i>Rules for the use of eye and face protectors</i>
BGR 195	<i>Rules for the use of gloves</i>

These information sheets can be purchased from Carl Heymann Verlag KG, Luxemburger Str. 449, D-50939 Köln, Germany

Particular emphasis is placed on the adherence to the following regulations => Attention!

- **The following persons are not allowed to operate these washers:**
 - *Pregnant or nursing women*
 - *Persons with chronic respiratory disorders or allergies*
 - *Persons under 16 years of age are only allowed to operate these washers under the supervision of a trained operator*
- *The operating instructions and the safety information must be read carefully before using the machine*

- *The operation instructions must be kept easily accessible near the machine*
- *Observe the respective information sheets of the trade co-operative association ¹ when working with solvents*
- *Local safety and accident prevention regulations always apply to the operation of the machine. These must be observed and adhered to.*
- *Rooms and areas with fire hazards must be marked according to paragraph 43, part 3 of the UVV (Accident Prevention Regulations) „General Regulations“*
- *Water used as a cleaning agent with or without additives must not be fed into the sewer system (Obtain information on this point from your local water authorities)*
- *Solvent spills must be dealt with according to water protection laws and regulations*
- *Adherence to maximal workplace concentrations according to the DIN-safety regulation sheets must be documented*
- *The maximal concentration limits according to „TA-Luft“² must be observed*
- *The exhaust must be connected whenever operating the machine to avoid the risk of fire, explosions and health impairment*
- *Only use approved solvents or cleaning agents -> see page 4*
- *Provisions must be made for protective clothing depending on how the machine is operated (gloves, eye protection, airway protection, whole body protection)*
- *Hands must be washed thoroughly before eating or drinking -> danger of poisoning*

Safety regulations pertaining to the installation of B-TEC machines (Hazardous Area Classification)

- *Open flames or other sources of ignition (e.g. welding or grinding apparatus) are not permitted within a 5 meter radius around the machine. Smoking is also prohibited!*
- *Fire hazard areas must be marked with the sign „Fire, open flames and smoking prohibited“. The prohibition sign is to show a burning match. The prohibition sign must be prominently displayed*
- *When working with highly flammable and flammable solvents, a special area fulfilling the requirements set down for rooms and areas with risk of fire must be present around the work space. All remaining areas with risk of explosion in which a hazardous explosive atmosphere can arise due to the local or factory conditions, are classified according to the Explosion Prevention Directive as:*

<i>Zone 0</i>	<i>the interior of the machine (only for a time/short-term)</i>
<i>Zone 1</i>	<i>within a radius of 2.5 meters (see VDE 0165, section 6.1)</i>
<i>Zone 2</i>	<i>within a radius of 2.5 to 5 meters (see VDE 0165, section 6.3)</i>

¹Berufsgenossenschaft

²Technische Anleitung zur Reinhaltung der Luft = Technical Instructions for the Prevention of Air Pollution

- The machine is delivered in carton
- Take the machine out of the carton and take it to the installation site

Requirements for the installation position: Notice !

- The gun cleaner is build for wall mounted .
- Horizontal industrial floor, if the machine is not for wall mounted. You also can take the B-TEC stand which have the art.-number: 65.40.20
- Dry and protected from frost
- Very well ventilated
- Adherence to the safety regulations pertaining to location (see point 6 of the operating instructions)
- Ambient temperature not below 5° C and not above 35 ° C
- **Attention to the official prescription for the floor, othetrwise take the B-TEC collecting basin for containers Art.-Nr.: 65.15.55**

Wall mounted:

Hole pattern as you see on **page 21** take on. (Please take a water balance !!). As the wall is builded, please take the adequate dowel min. 6 mm. Please take srews min. 5mm. Bring the srews in the dowel so that nearly of the srew head looks 10 mm out of the wall. Accumulate the gun cleaner on the wall and tight the srews. Attention that the door can close easily and while tight the srews the gun cleaner will not be cock.

Waste air: Notice!

- Connect the waste air hose with the hose clamp on the air exhaust connecting piece.
- The waste air hose must lead outdoors. One must ensure that the fumes are not led into areas where people are likely to be. The waste air must be exhausted safely. This means that it is not to be fed into chimneys serving furnaces or fireplaces and not into exhaust channels of spraying and drying cabinets
- **Attention!** Only use original B-TEC waste air hoses. Risk of fire if other hoses are used.

Mounting the black tube :

In the gun cleaner you find a black drain hose (23mm diameter). Please conect it with the hose clamp under the gun cleaner.

Compressed air connection: Notice!

- The facilities must hav one compressed air connection for each machine:



Operating pressure max: kPa / bar / (p.s.i.) 600 / 6 / (87)

Operating pressure min: kPa / bar / (p.s.i.) 500 / 5 / (73)

A pressure-regulating valve must be used if the compressed air connections do not have the required operating pressures. **Use only dry and oil-free air!!**

Grounding: Attention!

- There is a grounding cable on the air exhaust connecting piece. This must be electrostatically grounded, for example to a heating pipe
- According to local regulations proper grounding has to be assured with a separate ground cable (10 mm)



Notice ! ⇒ Please follow the set-up sequence exactly!!

Transport the washer to the installation site as described **on point 6 „Safety regulations pertaining to the installation of B-TEC machines“**, connect compressed air supply (**maximum 6 bar / 87 p.s.i.**) and attach the waste air hose.

Attention ! The safety regulations in section 6 must be read before and followed during installation.

The following solvent drums are required:

one 60 litre drum filled with 60 litres or one 30 litre drum filled with 30 litres.

Step one: insert the black drain hose (23mm diameter) and the grey intake to hose into the 60 litre (30 litre) drum that is used for waste solvent. (Circuit Solvent.)

The washer is now ready for use.

Step two: Operating the automatic washer section:

Open hinged door. The exhaust starts automatically. Then install tumbler-systems as described below:

- a) Remove lid of tumble-systems and place in the lid holder. Make certain that the paint-soiled inner surface faces downwards ⇒ towards the interior of the washer.
- b) The paint cup must be placed upside-down on the tumbler-holder
- c) The tumbler-system is now properly installed.
- e) Close the hinged door from the gun-cleaner
- f) Set timer for 1-3 minutes. The main cleaning cycle is activated. Solvent is drawn from the 60 litre drum and circulated. The timer can be reset to zero by hand. When the set time is over, open the hinged door slowly and check the cleaning results.

- g) The tumble-system is now clean. Reassemble and bring back into production.

Notice ! *Clean tumble-system immediately after each use.*

Notice ! *Before placing the tumble-system in the washer, remove lid from the paint cup and empty remaining paint into a collection container. The more thoroughly the cup is emptied, the longer the solvent can be used in the washer.*

Following these steps ensures optimal cleaning results.

Adjusting facilities:

On the right back of the gun cleaner you find a valve to adjust the speed of the pump.

10.Maintenance

Attention ! Disconnect the machine from the compressed air supply during cleaning and

maintenance.

- *We recommend cleaning of the stainless steel filter in the intake hose at regular intervals - at least at every solvent change. Defective filters must be replaced immediately.*
- *Clean perforated aluminium grates at regular intervals. Remove residues from drain pans to ensure rapid solvent run-off.*
- *When the machines are not to be operated for a longer period of time (for example during vacations) a clear rinse should be used after the final cleaning cycle so that the jets will not be clogged with heavily contaminated solvent.*
- *The operating permission expires if other than original B-TEC replacement parts are used.*

Kundenservice: Ihr Händler oder direkt bei:
Customer Service: Your dealer or directly at:

B-TEC North America
4901 Prime Parkway

McHenry, Illinois 60050

Phone: 815-759-1612
Fax: 815-759-1615
e-mail: sales@btecna.com

Item checked

	<i>OK.</i>	<i>Missing or faulty</i>	<i>Rechecked</i>
1. Operating instruc.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2. model designation label	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3. Warning signs	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
4. Conditions of fluid hoses	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5. Condition of compressed air hoses	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
6. Clean intake filters	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
7. Check washer cabinet for leaks	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
8. Function test of all control elements	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
9. Grounding of the gun cleaner	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

1. Name and address of expert technician

2. Safety inspection performed on:.....

Result of safety inspection:

- No faults, can be operated without restrictions
- Restricted operation, faults to be repaired by
- Operation not allowed, Re-inspection necessary

.....
Signed by expert technician

.....
lift user

After correctian faults:

.....
Signed by expert technicican

.....
lift user